

## SPEAK2 75

# The best professional speakerphone for hybrid working \*

- › Super-wideband audio and a full-range 65mm speaker
- › Four beamforming noise cancelling microphones
- › Voice Level Normalization equalizes all voices
- › Advanced Full Duplex audio powers natural conversations
- › Microphone Quality Indicator so you know you're being heard
- › Certified for leading virtual meeting platforms



|  |   |   |
|--|---|---|
| <b>General info</b>                                | Box contents  | Speakerphone, Link 380 Bluetooth adapter (variant dependent), carry pouch, safety information and warranty  |
|  | Packaging dimensions (WxHxD)                            | 153mm x 49mm x 155mm   6in x 1.9in x 6.1in  |
|  | Main unit dimensions (ØxH)                              | 132.5mm x 35mm   5.22in x 1.38in  |
|  | Main unit weight  | 466g   16.44oz  |
|  | IP rating **  | IP64-rated protection from dust and water   |
|  | Warranty  | 2 years   |
|  | Certifications and compliance ***                       | Microsoft Teams (variant dependent), Microsoft Teams Rooms (variant dependent), Microsoft Swift Pair, Alcatel-Lucent, Avaya, Cisco, Unify, MFi, Zoom Rooms, Zoom, Google Meet, Amazon Chime, Google Fast Pair |
| <b>Audio</b>                                       | Ideal for room sizes                                    | Up to 4.5m x 4.5m   14.76ft x 14.76ft   |
|  | Number of microphones                                   | 4   |
|  | Microphone type   | Digital MEMS  |
|  | Microphone frequency range                              | 150Hz - 14000Hz   |
|  | Microphone pick up range                                | Up to 2.5m   8.2ft  |
|  | Full Duplex   | Yes   |
|  | Signal-to-noise ratio (SNR)                             | 72 dB   |
|  | Speaker size  | 65mm   2.6in  |
|  | Peak audio output                                       | 88 dBspl @ 0.5m   |
|  | Speaker bandwidth (music mode)                          | 80Hz - 20000Hz  |
|  | Speaker bandwidth (speak mode)                          | 150Hz - 14000Hz   |
|  | Acoustic echo cancellation (AEC)                        | Yes   |
|  | Reverberation reduction                                 | Yes   |
|  | Voice Level Normalization (Automatic Gain Control, AGC) | Yes (for incoming and outgoing audio)   |
|  | Super-wideband (SWB) ****                               | Up to 16000 Hz  |
|  | Noise reduction on calls                                | Yes   |
| Microphone Quality Indicator (enable in Jabra app) | Yes   |   |
| <b>Software &amp; Apps</b>                         | Compatible software and/or apps                         | Jabra Direct, Jabra Sound+, Jabra Xpress  |
| <b>Battery</b>                                     | Talk time   | Up to 32 hours  |
|  | Corded charging   | Integrated USB C cable with USB A adapter   |
|  | Charging time (USB C/A 1 A)                             | Up to 2.5 hours   |
|  | Charging time (USB C/A 0.5 A)                           | Up to 5 hours   |
|  | Battery type  | Rechargeable lithium-ion battery  |
|  | Battery capacity  | 4700 mA   |

|                      |                                    |   |
|----------------------|------------------------------------|---|
| <b>Connectivity</b>  | Connectivity                       | USB C or USB A, Bluetooth (for smartphone/tablet only)                  |
|                      | Bluetooth adapter                  | USB-A   USB-C   |
|                      | Bluetooth® version                 | 5.2   |
|                      | Bluetooth® profiles                | A2DP, AVRCP, BLE (for Microsoft Swift Pair, Google Fast Pair), HFP, HSP |
|                      | Operating range (Bluetooth)        | Up to 30m   98ft  |
|                      | Paired devices                     | Up to 8 Bluetooth devices   |
|                      | Simultaneous Bluetooth connections | 2   |
|                      | Integrated USB cable length        | ca. 75cm   29.5in   |
| <b>Extended info</b> | Operating temperature              | 0°C to 40°C   32°F to 104°F   |
|                      | Storage temperature                | -20°C to 45°C   -4°F to 113°F   |

|                    |             |   |
|--------------------|-------------|---|
| <b>Products</b>    | 2775-209    | Jabra Speak2 75 - UC, Dark Grey                   |
|                    | 2775-329    | Jabra Speak2 75 - MS Teams - Link 380c, Dark Grey |
|                    | 2775-419    | Jabra Speak2 75 - UC - Link 380a, Dark Grey       |
|                    | 2775-429    | Jabra Speak2 75 - UC - Link 380c, Dark Grey       |
|                    | GSA2775-109 | Jabra Speak2 75 - MS Teams, Dark Grey             |
|                    | GSA2775-319 | Jabra Speak2 75 - MS Teams - Link 380a, Dark Grey |
| <b>Accessories</b> | 14101-90    | Jabra Speak2 75 Secure Mount                      |
|                    | 14208-10    | Jabra Kensington Lock Adaptor                     |
|                    | 14208-22    | Jabra Link 380c MS - USB-C - Bluetooth Adapter    |
|                    | 14208-24    | Jabra Link 380a MS - USB-A - Bluetooth Adapter    |
|                    | 14208-25    | Jabra Link 380c UC - USB-C - Bluetooth Adapter    |
|                    | 14208-26    | Jabra Link 380a UC - USB-A - Bluetooth Adapter    |

\* [jabra.com/commercial-claims](https://jabra.com/commercial-claims)

\*\* Avoid exposing the USB cable or adapter plug to moisture or liquids and never charge or power up if the USB cable or adapter plug is wet or moist.

\*\*\* Certified for USB connection or Jabra Link 380 Bluetooth adapter connection. Standard Bluetooth connections are not certified.

\*\*\*\* Requires a USB connection and all connected meeting participants to have a super-wideband supported device and conferencing app.

#### Jabra Speak2 75 Tech Sheet 27012023

Download the latest version of this document at:  
[jabra.com/support](https://jabra.com/support)